

HYDRAULIC TROLLEY JACK



CAPACITY RANGE	1.5 Ton to 3 Ton
TYPE	Hydraulic Trolley Jack
OPERATION	Manual Hydraulic
CONSTRUCTION	Heavy Duty Welded Steel Construction
APPLICATIONS	Automotive Lifting, Workshop Maintenance & Garage Service

FEATURES & BENEFITS

- Heavy-duty welded steel construction
- Compact and low-profile design
- Smooth hydraulic lifting operation
- Precision engineered lifting mechanism
- Wide saddle for improved load stability
- Durable front and rear wheels
- Long operating handle for effortless lifting
- High-quality hydraulic oil for reliable performance
- Powder-coated corrosion-resistant finish
- Easy manoeuvrability inside workshops
- Suitable for cars and light commercial vehicles
- Long service life with minimal maintenance

APPLICATIONS

- Passenger cars
- SUVs
- Light commercial vehicles
- Automotive workshops
- Service centres
- Fleet maintenance
- Tyre shops
- Vehicle inspection stations
- Industrial maintenance
- General garage applications

TECHNICAL SPECIFICATIONS

Model No.	Capacity (Ton)	Min Height (mm)	Max Height (mm)	Net/Gross Weight (kg)
HTJ-1.5	1.5	130	300	6.8 / 7.5
HTJ-2	2	135	340	8.7 / 9.4
HTJ-3	3	135	400	16.4 / 17

*Specifications subject to continuous product improvement without prior notice.

ESSENTIAL OPERATING GUIDELINES

- 1

Operate only on firm and level surfaces.
- 2

Position the saddle correctly beneath approved lifting points.
- 3

Never exceed the rated lifting capacity.
- 4

Always support the vehicle using jack stands before working underneath.
- 5

Inspect hydraulic oil, wheels and moving parts regularly.
- 6

Lower the load slowly and in a controlled manner.